

10/510462

REPLACED BY
ART 34 AMDT

1

MOPPING TROLLEYS

This invention relates to mopping trolleys and has particular reference to
5 mopping trolleys for facilitating the cleaning of a floor area is using a mop. In a
typical floor cleaning operation using a mop, the floor is first wetted with water
or with a cleaning liquid and is then mopped dry. In the drying operation, the
mop is wrung out or squeezed in order to remove surplus water, and is then
passed over the floor to take up and absorb the surplus water to dry the floor.
10 This operation can continue until the mop has become relatively and saturated
and is unable effectively to absorb water or liquid. At this stage the mop is
again squeezed to express surplus water and the mopping operation is repeated.

A typical mopping trolley comprises a wheeled carriage carrying a bucket with a
15 mop pressing disposed over the bucket which press is provided with lever means
to squeeze a mop head inserted in the press and to express surplus water into the
bucket. Our co-pending PCT Application No. GB00/01688 describes an
improved mop press which comprises first pressing means, second pressing
means and distortion means carried by at least one of pressing means
20 characterised that in use, with a mop head inserted between the pressing means,
the first and second pressing means are brought together to squeeze the mop
head, the arrangement being such that the distortion means in contact with the
mop head distorts in response to the uneven distribution of the mop head within
the press to permit pressure to be applied more uniformly over the surface of the
25 mop head whereby a substantial proportion of the liquid contained within the
mop head is expressed irrespective of the type and size of the mop head and
without needing to adjust the relative space between said first and second
pressing means.

30 This co-pending application referred to above is concerned with the problem of

REPLACED BY
ART 34 AMDT

how to express as much water as possible from the mop head during each "squeezing" operation. In using mopping systems of the type described above, however, the operative usually wets the floor using the waste water previously expressed into the bucket. While this has been a common practice for many years, the fact remains that it is more effective to clean a floor with clean water or cleaning fluid than it is using water or cleaning fluid that has already been used.

In order to overcome this problem, therefore, it has been proposed to have a two bucket system in which the two buckets are mounted in juxtaposition on a mopping trolley. The press is located over a waste water bucket to allow expressed waste water to fall into that bucket. The other bucket provides a supply of clean water.

It is an object of the present invention to increase cleaning efficiency by reducing the frequency with which an operative must return to a clean liquid replenishment station to charge the clean receptacle.

According to one aspect of the present invention there is provided a mopping trolley comprising carriage means capable of translation movement over a surface, a mop press assembly carried by said carriage means for expressing liquid from a mop head inserted into the press and at least two liquid receptacles, wherein a waste receptacle is arranged to receive waste liquid expressed from the mop press, and a clean receptacle is for providing a source of clean liquid for use in mopping.

In this way, clean liquid is available for mopping, and waste liquid expressed from the mop head is directed away to a separate waste receptacle. The receptacles will typically be a bucket, but could be other containers for liquid.

The liquid will typically be water and a detergent or other cleaning agent.

REPLACED BY
ART 34 AMDT

According to a preferred aspect of the invention the clean receptacle is located under the mop press so that a mop head may be dipped into the clean receptacle to be charged with clean liquid and lifted from the clean receptacle directly to the mop press for removal of excess charged fluid, the mop head being
5 maintained over the clean receptacle so that dripping excess fluid falls back to the clean receptacle below. In this way the amount of clean water wasted may be reduced, so that water dripping from the mop head falls back into the clean receptacle, rather than being conveyed to the waste receptacle before being used for cleaning. As less clean liquid is wasted, the efficiency of the cleaning
10 process is improved as fewer returns to the liquid replenishment station are necessary.

Preferably the waste receptacle is adapted to be in fluid communication with a discharge port from the mop press, whereby liquid expressed from the mop head
15 in the mop press is conveyed to the waste receptacle. In this way waste water is automatically diverted to the waste bucket, even though the press may not be located above the waste bucket. The fluid communication is preferably achieved by gravity feed. There may also be a liquid collector projecting from the waste bucket for catching fluid draining from the mop press.

20 Preferably the clean receptacle has a greater volumetric capacity than the waste receptacle. Typically the clean receptacle has a capacity that is at least 40% greater than the waste receptacle. In preferred embodiments of the invention, the clean receptacle has a capacity that is at least 50% greater than the waste
25 receptacle. We have found that by using, in a mopping trolley, buckets of dissimilar size, the efficiency of the mopping operation for a given size of trolley may be substantially improved.

In one embodiment of the trolley the waste and clean receptacles are located on
30 the trolley in a side-by-side arrangement so that the receptacles occupy a front

REPLACED BY
ART 34 AMDT

4

region of the trolley.

The waste trolley may be formed with a rim projection which extends under a mop press discharge port, thereby to collect fluid expressed from the mop press head by the mop press. The rim projection of the waste receptacle may nest with a corresponding recess in the clean receptacle so that the receptacles may sit adjacent one another.

A discharge port from the mopping press may be provided at one side of a bottom region of the mop press, so that liquid is discharged from one side of the mop press.

In another embodiment of the invention, the waste and clean receptacles may be located on the trolley in a front and rear (or fore/aft) arrangement so that the clean receptacle occupies a front region of the trolley, and the waste receptacle occupies a rear region of the trolley. In this embodiment the mop press may be provided with a discharge port that directs liquid expressed from a mop head generally rearwards into the waste receptacle. The discharge port may comprise a port formed at a rear end of a bottom region of the mop press.

20

A discharge port for the mopping press may be formed in an end cap attached to a bottom end region of the mop press. In this way a conventional mop press, or improved mop press of the type described in PCT/GB00/01688, may be adapted for use in the present invention, by modification by the attachment of a suitable end cap, such as a moulded plastics member.

25

Preferably the receptacles are removeably located on the trolley. Each receptacle may be removed independently of the other, for example for waste liquid discharge or clean liquid replenishment.

30

REPLACED BY
ART 34 AMDT

12 and 13 to express water from the mop head, which is discharged through an orifice 16 in the base of the receptacle defining the mop press 10. The water 17 expressed through orifice 16 is discharged into a waiting bucket 18. An identical bucket 19 (see Figure 1B) is disposed in side-by-side relationship with bucket 18 and contains fresh cleaning fluid for application to the floor by the mop.

First embodiment

In Figure 2, the mopping trolley in accordance with the present invention comprises a generally tubular frame 20 having a central upstanding portion 21 and a horizontal portions 22, which serves to form a base frame together with corresponding portions on the far side (not visible).

The frame 20 has, towards each corner (near two visible); a downwardly projecting portion 23 which carried at its lower end a caster indicated generally at 24. A base frame member 25 of the trolley carries a plastic tray 26 adapted to accommodate a pair of buckets 27 and 28 respectively. The buckets are disposed fore-aft, so that bucket 27 is at a front end region of the trolley (i.e. working side), whereas the bucket 28 is at a rear end region of the trolley. The bucket 27 has approximately twice the capacity of bucket 28 and is adapted to be filled with cleaning fluid for application to the floor by dipping a mop head into the fluid in bucket 27, shaking the surplus from the mop head back into the bucket and then applying the cleaning fluid to a floor to be cleaned in even stokes to distribute cleaning fluid thereover. After distribution of cleaning fluid the mop head (not shown in figure 2, but as shown in figure 1) may be returned to a mop press 10. The mop press is hung from a transverse space frame member 22. The mop press is then used to express dirty fluid from the mop head in the usual manner. The mop press has the general configuration of that shown in figure 1. However, the mop press is provided with an end cap 100 formed of moulded plastics material. The end cap is formed with a draining port 101 at a lower rear end region thereof. This drains over and directly into the rear bucket 27, as

REPLACED BY
ART 34 AMDT

shown in figure 2. In this way, waste water drain directly into the rear waste bucket, even though the mop press sits generally above and over the front clean bucket. The pressed mop may then be entered into the clean bucket for charging with cleaning fluid, and the cleaning process repeated.

5

Second embodiment

The embodiment shown in Figures 3 and 4 provides for a larger receptacle 37 and a smaller receptacle 38 to be accommodated in side-by-side relationship. Common features are numbered as per figures 1 and 2. In this embodiment, the physical height of each receptacle is the same but the volumetric capacity of the receptacle 37 is approximately twice that of the "waste" receptacle or bucket 38. The upper part of bucket 28 is provided with a lateral projection 40 towards the rear of bucket 38 and on one side thereof, the projection 40 being of a sufficient depth that water can be discharged into it without significant splashing. The base of the projection is closed to guide the water entering projection 40 (dashed lines in figure 3) into the main body of volume of receptacle 38. The larger container 37, which contains clean water and cleaning agent solution, is correspondingly shaped at 41 (see figure 4) to accommodate the projection 40 from the adjacent bucket, so that the two buckets nest together. The wall of the bucket 37 is shaped over its whole depth to accommodate the projection 40 of bucket 38. In this way, the "clean" bucket 27 can be removed from tray 25 without disturbing bucket 28.

In an alternative embodiment (not shown), a portion of the body of bucket 37 may be expanded to extend under the overlay portion 40 of bucket 38 thereby increasing the volume of the "clean" bucket 37 still further.

In this second embodiment, the mop press has an alternatively configured end cap 100. The end cap has a bottom side that is inclined down towards the waste bucket 38. A drain port 101 is formed at the side region of the end cap, so that

30

REPLACED BY
ART 34 AMDT

9

the port drains onto the projection 40 of the waste bucket. In this way the mop press drains directly into the waste bucket 38, whilst being located above the clean water bucket 37. Thus during the mopping process a mop head (not shown) may be taken from the mop press and allowed to drop back into the cleaning fluid bucket 37 without moving the mop head laterally from the waste bucket (as would be the case for a prior art arrangement in which the mop head was pressed over the waste bucket., as shown in figure 1B). This makes the mopping pressing and charging actions considerably more convenient for the operator.

10

The relatively shallow depth of the overlay portion 40 means that the bucket 38 can be removed easily, with bucket 27 remaining in place without requiring an operative to lift a heavy bucket full of water to a considerable height.

15 In both above embodiment, the relatively large size of the cleaning bucket ensures that few trips to water replenishment stations are necessary, thereby increasing the operative's effective cleaning time. The combination of bucket size differential, location of the mop press over the cleaning bucket and draining port orientation over the waste bucket provides enhanced mopping efficiency.

20

**REPLACED BY
ART 34 AMDT****Claims**

1. A mopping trolley comprising carriage means capable of translation movement over a surface, a mop press assembly carried by said carriage means
5 for expressing liquid from a mop head inserted into the press and at least two liquid receptacles, wherein a waste receptacle is arranged to receive waste liquid expressed from the mop press, and a clean receptacle is for providing a source of clean liquid for use in mopping.
- 10 2. A mopping trolley as claimed in claim 1 wherein the clean receptacle is located under the mop press so that a mop head.
3. A mopping trolley as claimed in claim 1 or claim 2 wherein the waste receptacle is in fluid communication with a discharge port from the mop press,
15 whereby fluid expressed from the mop head is conveyed to the waste receptacle.
4. A mopping trolley as claimed in any preceding claim wherein the clean receptacle has a greater volumetric capacity than the waste receptacle.
- 20 5. A mopping trolley as claimed in claim 4 wherein the clean receptacle has a capacity that is at least 40% greater than the waste receptacle.
6. A mopping trolley as claimed in claim 5 wherein the clean receptacle has a capacity that is at least 50% greater than the waste receptacle.
25
7. A mopping trolley as claimed in any preceding claim wherein the waste and clean receptacles are located on the trolley in a side-by-side arrangement so that the receptacles occupy a front region of the trolley.
- 30 8. A mopping trolley as claimed in claim 7 wherein the waste trolley is

REPLACED BY
ART 34 AMDT

11

formed with a rim projection which extends under the a mop press discharge port, thereby to collect fluid expressed from the mop press head by the mop press.

- 5 9. A mopping trolley as claimed in claim 8 wherein the rim projection of the waste receptacle nests with a corresponding recess in the clean receptacle so that the receptacles may sit in close proximity.
- 10 10. A mopping trolley as claimed in any preceding claim wherein a discharge port from the mopping press is provided at one side of a bottom region of the mop press, so that liquid is discharged from one side of the mop press.
- 15 11. A mopping trolley as claimed in any of claims 1 to 6 wherein the waste and clean receptacles are located on the trolley in a front and rear arrangement so that the clean receptacle occupies a front region of the trolley, and the waste receptacle occupies a rear region of the trolley.
- 20 12. A mopping trolley as claimed in claim 11 wherein the mop press is provided with a discharge port that directs liquid expressed from a mop head generally rearwards into the waste receptacle.
13. A mopping trolley as claimed in claim 12 wherein the discharge port comprises a port formed at a rear end of a bottom region of the mop press.
- 25 14. A mopping press a claimed in any preceding claim wherein a discharge port for the mopping press is formed in an end cap attached to a bottom end region of the mop press.
- 30 15. A mopping press as claimed in any preceding claim wherein the receptacles are removeably located on the trolley and the each receptacle may be

REPLACED BY
ART 34 AMDT

removed independently of the other, for example for waste liquid discharge or clean liquid replenishment.